

Concrete Gas-Nailer CN40-G643E

for KMR steel nails strips



- adjustable penetration depth
- levelling foot for 90° nailing
- protective cap for sensitive surfaces
- rafter hanger

Applications:

Carpenters, roofers, timber frame construction, e.g. for fastening boards, roof battens, crates, pallets, visible boarding with oval head nails and nail screws

Included in delivery: Sturdy case, one Li-Ion battery, charger, spare parts list, service instructions, exploded drawing, allen wrench, ear plugs



Follow KMR on








CN40-G643E

Technical data

Code	12100701
Dimensions in mm	L 327, W 130, H 385
Weight	3.8 kg
Operation mode	Fuel cell
Safety system	Single sequential actuation
Battery charging time and voltage	90 minutes - 7.2 Volt - 2500 mAh
Fastener type	Steel nails
Diameter	2.6-3.0 mm
Length	15 – 40 mm
Magazine capacity	40 nails
Average number of shots per battery load	8000
Average number of shots per fuel cell	1.200
Emission sound pressure level at workstation	L pA, 1s = 101.5 dB
Single-shot emission sound pressure level	L pA, 1s = 104.1 dB
Vibration level as per ISO 8662-11 is 2.83 m/s2	

Subject to technical changes



KMR Steel nail strips

Diameter 2.6-3.0 mm

15-40 Length

The Behrens group is a member of the following associations:











Fuel cell (40g. 80 ml.)





















Follow KMR on