

D34/90-G641E

gas operated D-head nailer

for KMR strip nails P34° D-head
paper and plastic collated



Li-Ion battery with
LED charge indicator



Properties:

- high capacity Li-Ion battery with LED charge indicator
- light and well balanced
- depth adjustment
- extremely powerful
- anti-slip nose
- protective cap for sensitive surfaces
- rafter hanger

Applications:

Carpenters, roofers, timber frame construction...

Included in delivery: Sturdy case, one Li-Ion battery, charger, spare parts list, service instructions, exploded drawing, allen wrench, ear plugs






D34/90-G641E

Technical data

| | |
|--|----------------------------------|
| Code | 12100699 |
| Dimensions in mm | L 382, W 108, H 377 |
| Weight | 3.68 kg |
| Operation mode | Fuel cell |
| Safety system | Single sequential actuation |
| Battery charging time and voltage | 90 minutes - 7,2 Volt - 2500 mAh |
| Fastener type | D-head nails |
| Diameter | 2.87-3.3 mm |
| Length | 50 - 90 mm |
| Magazine capacity | 60 nails |
| Average number of shots per battery load | 8000 |
| Average number of shots per fuel cell | 1.200 |
| Emission sound pressure level at workstation | L pA, 1s = 96,2 dB |
| Single-shot emission sound pressure level | L pA, 1s = 101 dB |
| Vibration level as per ISO 8662-11 is | 2,67 m/s ² |

Subject to technical changes



D-head nails P 34° paper and plastic collated

| | |
|----------|---|
| Diameter | 2.87-33 mm |
| Length | 50- 90 mm |
| Material | BK = steel, bright NK = steel, electroplate galvanized RF = stainless steel, comparable to material 1.4301 NR = stainless steel, comparable to material 1.4401 FV = steel, hot dipped galvanized Smooth, ring shank, screw shank * |

Surface
properties



Fuel cell (40g. 80 ml.)

* Further types available on request
Nails available according to DIN 1052, as
well as EN14592 (Eurocode 5)



**The Behrens group is a member of
the following associations:**



ZimmerMeisterHaus
So geht Holzbau
Ein Marktpartner der ZimmerMeisterHaus-Gruppe

KMR - The partner of craftsmen

Joh. Friedrich Behrens AG, Bogenstraße 43-45, 22926 Ahrensburg
Tel. +49 (0) 4102 78 - 444, Fax +49 (0) 4102 78 - 270
info@kmr-group.de, www.kmr-group.de

Follow KMR on



KMR UK & Ireland